

# SHIBAURA

**Riding Greens Mower** 

- \*\*Bucket is standard equipment.
  \*\*Available with grooming and brush & thatching.

# Light weight, high precision!

High-powered engine!

## Reduce damage to the green

Low installation pressure (0.58kg/cm²) achieved by reducing vehicle weight and adopting 19-inch wide tires.

## Safe driving

The reel pull-up position is higher than that of conventional machines, so there is no need to worry about hitting obstacles while traveling.

## Easy to maintain



- Swing-out mechanism is adopted. Easy maintenance such as wrapping of the mid-mower unit.
- Full-open cover allows for easy maintenance of the engine.

## Adopts a variable bed knife offset mechanism

(Various settings are available according to the condition of the green.)

Mowing position and amount of bite of turf would be adjustable.

"To manage turf care including removing thatch",

"to reduce grass stucking",

"to create striped patterns",

opitimal turf management is possible depending on the place, person and purpose.

Example: When the mowing height is set to 4.0 mm

and creates clear striped patterns.

### Offset 8

Reduces grass stucking A setting that produces characteristics between offset 6 and offset 10.

### Offset 10

It bites into the turf well and is suitable for low mowing.





	Specifications			
Model name			MG70G	
Dimension	Length(mm)		2,120	
	Width(mm)		1,840	
	Height(mm)		1,370	
	Wheelbase (mm)		1,285	
	Wheel track Front tire(mm)		1,050	
	Clearance (mm)		120	
Tire	Front tire		19×10.5-8 4PR	
re	Rear tire		18×9.5-8 4PR	
Engine	Brand name		Vanguard	
	Туре		Vtype2cylinder aircooling 4 cycle petrol	
	Number of cylinder		2cylinder	
	Displacement(cc)		627	
	Power (kW (PS)/rpm)		14.9(20)/3600	
Drive system	Transmission type		HST non-stage	
	Braking system		Internal expandable brake	
	Steering		Full hydraulic power steering	
	Speed	forward (Km/h)	0 ~ 14.0	
		reverse (Km/h)	0 ~ 6.8	
	Weight (kg) (dry)		392	
Capacity	Fuel tank(L)		20	
	Oil tank(L)		23	
ίţγ	Battery		38B20R	
Reel mower	Width of reel(mm)		1,525	
	Reel cylinder(mm)		φ123	
	Number of blades		11	
	Cutting height(mm)		~ 30	
Working capacity (a/h)			Operating speed 6km/h, efficiency 0.8	



• Improper use of any product may cause serious or fatal injury. Read carefully the operating and safety instructions in your owner's manual before use. \*We reserve the right to discontinue models or change specifications without notice.

## **IHI Agri-Tech Corporation**

TEL; + 81 123 26 2210 FAX; + 81 123 26 2412 URL; https://www.ihi.co.jp/iat/en/

