

Ride-On 5-Gang Rotary Mower

# SM888

The lightest one in the class of 5-gang rotary mower,  
with new designed rotary deck,  
achieves beautiful cutting finish

# SHIBAURA



# IHI


Realize your dreams

Climbing power and driving performance have been improved by the drive system “SMD” that applies Shibauro's tractor technology. “SMD” also helps save maintenance costs and reduce the risk of oil leaks.




Manufactured to exacting standards in Japan and powered by SHIBAURA's own diesel engine, SM888 will give years of durable service.





## New designed Rotary deck

Rotary blade seeks to reduce resistance and cut beautifully. An anti-sculpt has been installed in the groove to prevent galling. The deck is made deeper and not clogged. There is also a function to control the flight of the mowed grass to the left and right.




## Adjust the cutting height easily

The height can be adjusted at 3 places per unit. Therefore it isn't necessary to prepare a lot of tools.



## Flip up function

Flip-up function is installed into each unit on the front (No.1) and both sides (No.4 & 5). You can easily clean up the interior rotary deck and the rotary blade can be easily inspected and replaced.



## “SMD” provides you with ideal driving

“SMD, Shibaura Mechanical Drive” is Shibaura’s own driving system technology that directly transmits power with the combination of gear transmission and HST without using a hydraulic driving motor.

Climbing power and stable driving performance have been rapidly improved. “SMD” enables mower to run smoothly on the hills and you can work at 20 degrees slopes. “SMD” reduces the risk of oil leakage as well as saves the maintenance costs.

In addition, it is approximately 30% more efficient in fuel consumption than the oil pressured 5 Reel Mower. \*According to our test results.





## Deluxe Seat

In order to reduce the burden on workers and provide all operators with comfortable environment at all times, ergonomic deluxe seat is installed.

- Height Adjustment
- Reclining
- Weight Adjustment
- Armrest Height Adjustment
- Suspension
- Headrest (option)

## Specifications

Model		SM888	
Dimensions	Overall length	mm 3,100	
	Overall width	mm Working:2,450 / Moving:2,070	
	Overall height	mm 2,050	
	Ground clearance	160	
Mass	kg	1,580	
Engine	Model	Shibaura N844L-D(diesel)	
	Total swept volume	cc 2,216	
	Output	kW(PS)rpm 33.1(45.0)/2,700	
	Fuel capacity	ℓ 41	
Drive	System	HST Hydraulic stepless shift auto/full -4wd	
	Shift	Sub shift 2 speed	
	Vehicle speed	km/h	Forward L:0~11.8 H:0~17.1
			Reverse L:0~8.3 H:0~11.9
Steering		Power steering	
Mower	Number of teeth	1/1 unit	
	Total cutting width	mm 2,280	
	Mowing height	mm 20~95(5mm pitch)	
	Number of unit	5	
Work ability	m <sup>2</sup> /h	16,440 (Working speed 9km/h efficiency=0.8)	

### Important information

● Improper use of any product may cause serious or fatal injury. Read carefully the operating and safety instructions in your owner's manual before use.  
 ※ We reserve the right to discontinue models or change specifications without notice.

 **SHIBAURA**

**IHI Agri-Tech Corporation**

TEL ; + 81 123 26 2210 FAX ; + 81 123 26 2412

GENERAL CONTACT ; dept2@iat.ihigrp.co.jp

URL ; <https://www.ihico.jp/iat/en/>

